

# General Information

## Specifications



Storage Systems

**Dimensions:**

Maximum width is 96", maximum depth 24", and maximum height is 48" for wood grain material or 56" for solid color. Dimensions are based on the number of openings and size of totes that are ordered.

Unit is constructed using  $\frac{3}{4}$ " thick particle board with thermofused melamine or High Pressure Laminate on both sides. Edges are finished using 3mm PVC. Adjustable shelves have pockets routed in the bottom to prevent the shelves from sliding out. Tote openings will vary depending on the unit and tote size.

**Assembly:**

Each unit is factory assembled using dowel construction. Tote bins are sold separately.

**Shipping Class:**

100



Mail Slots

**Dimensions:**

Mail Slot Dimensions: Multiple

Widths: 24", 36", or 48"

Depth: 14"

Height: 36" or 48"

Base Cabinet Dimensions: Multiple

Widths: 24", 36", or 48"

Depth: 23"

Height: 23"

Unit case is constructed using  $\frac{5}{8}$ " nominal and  $\frac{3}{4}$ " thick particle board with thermofused melamine or High Pressure Laminate on both sides. Shelves are  $\frac{5}{8}$ " thick particle board with thermofused melamine or High Pressure Laminate. Edges are finished using 3mm PVC. Adjustable shelves have pockets routed in the bottom to prevent the shelves from sliding out. Opening size will vary depending on the amount of shelves and size of the unit. A 36" tall unit comes with 7 shelves per column opening to make 8 openings. A 48" tall unit comes with 10 shelves per column opening to make 11 openings.

**Assembly:**

Each unit is factory assembled using dowel construction. Mail storage and base cabinets can be purchased separately. A high pressure laminate countertop is sold separately if needed.

**Shipping Class:**

100



Tall Cubbies

**Dimensions:**

Widths: 24", 36", or 48"

Depth: 14"

Height: 48", 60", or 72"

Unit is constructed using  $\frac{3}{4}$ " thick particle board with thermofused melamine or High Pressure Laminate on both sides. Upper and lower fixed shelves are optional. Edges are finished using 3mm PVC. Opening size will vary depending on the amount of dividers and width of the unit. One double prong coat hook will be provided per 12" of width. Coat hooks are mounted with a steel threaded insert to prevent hooks from pulling out. If units are wall hung we recommend using the steel base structure. Steel base structure consists of 16-gauge steel wall mount angle brackets and 16-gauge sheet steel powder coated black.

**Assembly:**

Each unit is factory assembled using dowel construction. Steel base structure is field installed. Cubbies and base structures are sold separately.

**Shipping Class:**

100

**Dimensions:**

Widths: 24", 36", or 48"

Depth: 14"

Height: 16"

Unit is constructed using  $\frac{3}{4}$ " particle board with thermofused melamine or High Pressure Laminate on both sides. Units are available with a curved or straight side panel. Edges are finished using 3mm PVC. Openings size will vary depending on the amount of dividers and width of the unit. One double prong coat hook will be provided per 12" of width. Coat hooks are mounted with a steel threaded insert to prevent hooks from pulling out.

**Assembly:**

Each unit is factory assembled using dowel construction.

**Shipping Class:**

100



Wall Cubbies